

GAUGES



Model 41 OEM Gauges (Single Scale)

2 1/2" Case

Center Back or Bottom Mount

These gauges are designed for use with any medium not corrosive to brass or bronze. Liquid-filled gauges are recommended for reducing shock caused by pressure fluctuations or vibration.

STANDARD RANGES









Standard gauge scales - PSI Only

STANDARD DIAL RANGES	AVAILABILITY	GRADUATION	
		Major	Minor
PSI	2-1/2"		
0-30" VAC	✓	5	.5
30"-0-60 psi	✓	10	1
30"-0-100 psi	✓	20	2
0-15 psi	✓	5	.5
0-30 psi	✓	5	.5
0-60 psi	✓	10	1
0-100 psi	✓	20	2
0-160 psi	✓	20	2
0-200 psi	✓	20	2
0-300 psi	✓	50	5
0-400 psi	✓	100	10
0-600 psi	✓	100	10
0-1000 psi	✓	200	20
0-1500 psi	✓	200	20
0-2000 psi	✓	500	50
0-3000 psi	✓	500	50
0-4000 psi	✓	500	50
0-5000 psi	✓	1000	100
0-6000 psi	✓	1000	100

FEATURES	
MOVEMENT:	Brass
BOURDON TUBE:	C-Shaped in phosphor bronze up to 1000 psi and Helical in phosphor bronze above 1000 psi
POINTER:	Black enameled aluminum
DIAL:	White aluminum
WINDOW:	Acrylic
CASE MATERIAL	304 Stainless steel
CONNECTION MATERIAL	Brass
CONNECTION SIZE	1/4" MNPT
ACCURACY	ASME/ANSI B40.1 Grade B (3-2-3%)

PRICING AND OPTIONS - (Stock)	
2-1/2" CASE Call for Pricing
U-Clamp	2440-UC . . . Call for Pricing
Front Flange	2330/40-FF . Call for Pricing
4" CASE Call for Pricing
U-Clamp	4440-UC . . . Call for Pricing
Front Flange	4330/40-FF . Call for Pricing

CASE STYLES AND DIMENSIONS

CASE STYLE	IMAGE	DIMENSIONS	SIZE	A	B	C	D	E
			2-1/2"	2.670"	1.100"	2.270"	2.460"	n/a
BOTTOM MOUNT Style 1								
BACK MOUNT Style 2	 Special Order*		SIZE	A	B	C	D	E
			2-1/2"	2.630"	1.120"	2.214"	2.470"	n/a
FRONT FLANGE Style 3	 Special Order*		SIZE	A	B	C	D	E
			2-1/2"	2.670"	1.100"	2.270"	2.460"	3.340"
PANEL MOUNT Style 4	 Special Order*		SIZE	A	B	C	D	E
			2-1/2"	2.670"	1.100"	2.270"	2.460"	3.540"

* Back mount case styles (Style 2, 3 and 4) are available by special order. Please call for details

ORDERING INFORMATION

To determine the ordering number, use the following information

Example - 2241GXB3000 = 2-1/2", 1/4 CBM, OEM, Glycerin-filled, Stainless Case, 3000 PSI

1 st Digit	2 nd Digit	3 rd & 4 th Digits	5 th Digit	6 th Digit	7 th Digit	Range	Suffix
Dial Size	Case Style	Model	Fill Material	Case Material	Wetted Parts	PSI	Options
2 = 2.5"	1 = Bottom 2 = Back* 3 = Front Flange* 4 = Panel Mount*	41 = OEM	D - Dry G - Glycerin	X = Stainless	B = Copper Alloy	SEE RANGE CHART	Custom Logo Color Dial Special Dial Etc.