

GAUGES



Model 54 All Stainless OEM Gauges (Single Scale)

2 1/2" or 4" Case

Center Back or Bottom Mount

These gauges are designed for use with any medium not corrosive to stainless steel. Liquid-filled gauges reduce shock caused by pressure fluctuations or vibration.

STANDARD RANGES*

Standard Gauge Scales - PSI Only.

STANDARD DIAL RANGES	AVAILABILITY		GRADUATION		
	PSI	2-1/2"	4"	Major	Minor
0-30" VAC		✓	✓	5	.5
0-30 psi		✓	✓	5	.5
0-60 psi		✓	✓	10	1
0-100 psi		✓	✓	20	2
0-160 psi		✓	✓	20	2
0-200 psi		✓	✓	50	5
0-300 psi		✓	✓	50	5
0-400 psi		✓	✓	100	10
0-600 psi		✓	✓	100	10
0-1000 psi		✓	✓	200	20
0-1500 psi		✓	✓	200	20
0-2000 psi		✓	✓	500	50
0-3000 psi		✓	✓	500	50
0-5000 psi		✓	✓	1000	100
0-6000 psi		✓	✓	1000	100
0-10000 psi		✓	✓	2000	200









*Limited availability on some sizes and ranges

FEATURES	
MOVEMENT:	Stainless Steel
BOURDON TUBE:	316 Stainless Steel
POINTER:	Black enameled aluminum
DIAL:	White aluminum
WINDOW:	Polycarbonate
CASE MATERIAL	304 Stainless steel
CONNECTION MATERIAL	316 Stainless steel
CONNECTION SIZE	1/4" MNPT Standard.
ACCURACY:	ASME/ANSI B40.1 Grade B (3-2-3%)

PRICING AND OPTIONS - (Stock)

2-1/2" CASE Call for Pricing
U-Clamp	2454-UC ... Call for Pricing
Front Flange	2354-FF Call for Pricing
4" CASE Call for Pricing
U-Clamp	4454-UC . . . Call for Pricing
Front Flange	4330/54-FF . Call for Pricing

CASE STYLES AND DIMENSIONS

BOTTOM MOUNT Style 1			SIZE	A	B	C	D	E
			2-1/2"	2.672"	1.109"	2.25"	2.460"	n/a
			4"	4.344"	1.828"	3.391"	3.970"	n/a
BACK MOUNT Style 2			SIZE	A	B	C	D	E
			2-1/2"	2.672"	1.109"	2.25"	2.460"	n/a
			4"	4.344"	1.828"	3.391"	3.970"	n/a
FRONT FLANGE Style 3			SIZE	A	B	C	D	E
			2-1/2"	2.672"	1.109"	2.25"	2.460"	3.343"
			4"	4.35"	1.91"	3.41"	3.970"	5.19"
PANEL MOUNT Style 4			SIZE	A	B	C	D	E
			2-1/2"	2.672"	1.109"	2.25"	2.460"	3.359"
			4"	n/a	n/a	n/a	n/a	n/a

ORDERING INFORMATION

To determine the ordering number, use the following information

Example - 4154GXX2000 = 4", 1/4" Btm Mt., All Stainless, Glycerin-filled, Stainless Case, 2000 PSI

4	1	50	G	X	X	2000	
1 st Digit	2 nd Digit	3 rd & 4 th Digits	5 th Digit	6 th Digit	7 th Digit	Range	Suffix
Dial Size	Case Style	Model	Fill Material	Case Material	Wetted Parts	PSI	Options
2 = 2.5" 4 = 4"	1 = Bottom 2 = Back 3 = Front Flange 4 = Panel Mount	54 = Stainless	D = Dry G = Glycerin S = Silicone F = Florolube	X = Stainless	X = Stainless	SEE RANGE CHART	Custom Logo Color Dial Special Dial Etc.