

GAUGES



Model 58
All Stainless Gauges
Welded Connection
Field Repairable
(Single Scale)

4" Case Only

Bottom Mount Only

These gauges are designed for use with any medium not corrosive to stainless steel. Liquid-filled gauges are recommended for reducing shock caused by pressure fluctuations or vibration.

STANDARD RANGES



Standard gauge scales - PSI Only

STANDARD DIAL RANGES	AVAILABILITY	GRADUATION	
		Major	Minor
PSI	4"		
0-30" VAC	✓	5	.5
0-15 psi	✓	2	.2
0-30 psi	✓	5	.5
0-60 psi	✓	10	1
0-100 psi	✓	20	2
0-160 psi	✓	20	2
0-200 psi	✓	50	5
0-300 psi	✓	50	5
0-400 psi	✓	100	10
0-600 psi	✓	100	10
0-1000 psi	✓	200	20
0-1500 psi	✓	200	20
0-2000 psi	✓	500	50
0-3000 psi	✓	500	50
0-5000 psi	✓	1000	100
0-10000 psi	✓	2000	200
0-15000 psi	✓	2000	200
0-20000 psi	✓	2000	200

FEATURES	
MOVEMENT:	Stainless Steel
BOURDON TUBE:	316 Stainless Steel
POINTER:	Black enameled aluminum
DIAL:	White aluminum
WINDOW:	Polycarbonate
CASE MATERIAL	304 Stainless steel
BEZEL	304 Stainless steel, Bayonet type.
CONNECTION MATERIAL	316 Stainless steel
CONNECTION SIZE	1/2" MNPT Standard
ACCURACY:	ASME/ANSI B40.1 Grade 1A (1%)

PRICING AND OPTIONS - (Stock)	
4" CASE Call for Pricing

CASE STYLES AND DIMENSIONS

BOTTOM MOUNT Style 1			SIZE	A	B	C	D	E
			4"	4.344"	1.828"	3.391"	3.970"	n/a

ORDERING INFORMATION

To determine the ordering number, use the following information

Example - 4158GXX200 = 4", 1/2" Btm Mt., All Stainless - Field Repairable, Glycerin-filled, Stainless Case, 200 PSI

4	1	58	G	X	X	200	
1 st Digit	2 nd Digit	3 rd & 4 th Digits	5 th Digit	6 th Digit	7 th Digit	Range	Suffix
Dial Size	Case Style	Model	Fill Material	Case Material	Wetted Parts	PSI	Options
4 = 4"	1 = Bottom	58 = Stainless Field Repairable	D - Dry G - Glycerin S - Silicone F - Florolube	X = Stainless	X = Stainless	SEE RANGE CHART	Custom Logo Color Dial Special Dial Etc.