

GAUGES

Model 60 Low Pressure Gauges



2 1/2" or 4" Case

Bottom Mount Only

These gauges are designed for use with any medium not corrosive to bronze and pressures up to 10 PSI.

AVAILABLE RANGES



Available gauge scales - Inches of water, MM of water or Oz. /in²

FEATURES	
MOVEMENT:	Brass
DIAPHRAGM:	Sensitive phosphor bronze
POINTER:	Black enameled aluminum
DIAL:	White aluminum
WINDOW:	Acrylic
CASE MATERIAL	Steel, Black Painted
CONNECTION MATERIAL	Brass
CONNECTION SIZE	1/4" MNPT on all sizes.
ACCURACY:	ASME/ANSI B40.1 Grade A (2-1-2%)

STANDARD DIAL RANGES	AVAILABILITY		GRADUATION	
	2-1/2"	4"	Major	Minor
0-15" (inches of water)	✓	✓	1"	.1"
0-30" (inches of water)	✓	✓	5"	.25"
0-60" (inches of water)	✓	✓	5"	.5"
0-100" (inches of water)	✓	✓	10"	1"
0-200" (inches of water)	✓	✓	20"	2"
0-5 psi	✓	✓	1 psi	.1 psi
0-10 psi	✓	✓	1 psi	.1 psi

PRICING AND OPTIONS - (Non-Stock)	
2-1/2" CASE Call for Pricing
4" CASE Call for Pricing

CASE STYLES AND DIMENSIONS

BOTTOM MOUNT Style 1			SIZE	A	B	C	D	E
			2-1/2"	2.468"	1.188"	1.828"	n/a	n/a
			4"	3.968"	1.266"	2.734"	n/a	n/a

ORDERING INFORMATION

To determine the ordering number, use the following information

Example - 4160DSB10 = 4", 1/2" Btm Mt., Low Pressure, Dry, Steel Case, 10 PSI

4	1	51	G	X	X	200	
1st Digit	2nd Digit	3rd & 4th Digits	5th Digit	6th Digit	7th Digit	Range	Suffix
Dial Size	Case Style	Model	Fill Material	Case Material	Wetted Parts	PSI	Options
2 = 2.5" 4 = 4"	1 = Bottom	60 = Low Pressure	D - Dry	S = Steel	B = Copper Alloy	SEE RANGE CHART	Custom Logo Color Dial Special Dial Etc.